

## FIRE PROTECTIVE BUILDING PRODUCTS

HEAD OFFICE: AUCKLAND (09) 579 0367

CHRISTCHURCH (03) 379 9364

[www.firepro.co.nz](http://www.firepro.co.nz) [sales@firepro.co.nz](mailto:sales@firepro.co.nz)

Product specifications can change. Contact us to ensure you have our latest datasheet

## CERAMIC FELT GLAZING TAPE

### FIREPRO CF1003 & CF2003

#### DESCRIPTION

Firepro Ceramic Felt Tape is used where wired glass or fire rated glass is installed in a steel frame. It provides a non-combustible cushion for the glass. It is used in conjunction with Firepro M707 intumescent sealant.

The ceramic felt tape is 2mm - 3mm thick and comes in 10M rolls either 10mm or 20mm wide. The ceramic felt has a double sided adhesive tape on one face. In some situations two layers of ceramic felt are used.

CF1003      10mm wide.  
CF2003      20mm wide.

#### LIMITATIONS

1. Where intumescent felt is required use Firepro FIS Intumescent Strip.
2. Ceramic Felt is not recommended for use in glassed timber systems.

Firepro stock several products for this use:

System 90  
System 36  
FIS Strips  
PAL Strips  
Intustrip  
Flexpress SA Seal

3. Fire test certificates can not be provided as for ceramic felt as it has been fire tested as part of proprietary fire rated window systems.